



Specification

| | |
|--|--|
| Model | SH-VDO-216 |
| Temp Range | Ambient +5°C to 250°C (Ambient + 9°F to 482°F) |
| Time Range | 00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer |
| Vacuum Resistance | 0 to 76 cmHg |
| Temp & Time Controller | Microprocess Digital P I D Membrane touch controller |
| Heater Capacity | 4500 W |
| Dimension Internal (WxDxH) | 600x600x600(mm) 23.62x23.62x23.62(inch) |
| Dimension External (WxDxH) | 915x880x1150(mm) 36.02x34.64x45.27(inch) |
| Weight | 281 Kg |
| Capacity | 216 L |
| Material Internal | Stainless Steel |
| Material External | Steel Plate with Powder Heating Coated |
| View Window | Tempered Glass |
| Shelves | 5 Supplied (7 Maximum) |
| Electrical Requirements 120V ,50/60Hz, 1 | 37.5 A |
| Material Packing | Silicon Rubber Packing |
| Electrical Requirements 230V,50/60Hz, 1 | 19.6 A |

Feature

- Over temp controller
- Automatic reset function incoming power cut
- Buzzer on when set Time arrived
- Electric leakage circuit breaker

Option

- Programmable Controller
- RS-485 interface
- RS-232C interface