



## Specification

Model	SH-VDO-216
Temp Range	Ambient +5°C to 250°C (Ambient + 9°F to 482°F)
Time Range	00.00 to 99HR 59MIN (MIN SEC) Selectable Digital Counter Timer
Vacuum Resistance	0 to 76 cmHg
Temp & Time Controller	Microprocess Digital P I D Membrane touch controller
Heater Capacity	4500 W
Dimension Internal (WxDxH)	600x600x600(mm) 23.62x23.62x23.62(inch)
Dimension External (WxDxH)	915x880x1150(mm) 36.02x34.64x45.27(inch)
Weight	281 Kg
Capacity	216 L
Material Internal	Stainless Steel
Material External	Steel Plate with Powder Heating Coated
View Window	Tempered Glass
Shelves	5 Supplied (7 Maximum)
Electrical Requirements 120V ,50/60Hz, 1	37.5 A
Material Packing	Silicon Rubber Packing
Electrical Requirements 230V,50/60Hz, 1	19.6 A
LED Lamp	DC 24V, 1.2W, LED bar, Waterproof, Cool White

## Feature

- Over temp controller
- Automatic reset function incoming power cut
- Buzzer on when set Time arrived
- Electric leakage circuit breaker

## Option

- Programmable Controller
- RS-485 interface
- RS-232C interface